QC11Y | Guillotine Type Hydraulic Shearing Machine



Features:

1) Solid design and durable body for precise cutting results.
2) Both blade gap and cutting angle could be adjusted.
3) 3 points supported rolling guide, eliminate the support gap to improve the cutting precision.
4) Back stroke with accumulator
5) With counter and safety barrier



3 points supported rolling guide, eliminate the support gap to improve the cutting precision. Blade gap and cutting angle are both adjustable. Rectangular type blade with 4 cutting edges.



Back gauge is fixed on the upper blade carrier, can straight move with the blade carrier. Forward and back moving is controlled by A/C motor and ball screw, position can be showed on the E21s system screen. Accuracy 0.1mm.



Ball transfer table with front support arms. There are movable stop blocks on the arm to show the numbers on the rule, easy for thin sheet cutting. Blade safety guard is standard equipped.



Electric cabinet with reliable electric parts as Schneider electrics. Electric diagram will be provided in the operation manual for future maintenance and repairing.



E21s NC system: backgauge control, control for general AC motor or frequency inverter. Intelligent positioning, one side positioning. Program memory of up to 40 programs and 25 steps per program. 160x160 LCD display.



Holding fingers are provided to ensure that the plate is held firmly along the length of the cutting area. Each independently acting holding fingers is capable of applying high pressure to hold the material being cut at the same time.



Rexroth brand valve



Siemens brand motor



Sunny brand gear pump

SPECIFICATIONS

Items	unit	QC11Y-6x2500	QC11Y-6x3200	QC11Y-6x4000
Max. cutting thickness	mm	6	6	6
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-1.5	0.5-1.5	0.5-1.5
Travel distance of back gauge	mm	20-550	20-550	20-600
Throat depth	mm	150	150	150
Stroke speeds	spm	16-26	12-22	10-20
Main motor	kW	7.5	7.5	7.5
Length	mm	3000	3700	4800
Width	mm	1500	1650	1650
Height	mm	2000	2050	2250

Items	unit	QC11Y-8x2500	QC11Y-8x3200	QC11Y-8x4000
Max. cutting thickness	mm	8	8	8
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-2	0.5-2	0.5-2
Travel distance of back gauge	mm	20-600	20-600	20-600
Throat depth	mm	150	150	150
Stroke speeds	spm	14-25	12-20	10-20
Main motor	kW	11	11	11
Length	mm	3040	3860	4800
Width	mm	1700	1700	1800
Height	mm	2150	2350	2480

Items	unit	QC11Y-10x2500	QC11Y-10x3200	QC11Y-10x4000
Max. cutting thickness	mm	10	10	10
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-1.5	0.5-1.5	0.5-1.5
Travel distance of back gauge	mm	20-600	20-600	20-600
Throat depth	mm	150	150	150
Stroke speeds	spm	12-20	10-20	10-18
Main motor	kW	11	15	15
Length	mm	3040	3860	4800
Width	mm	1700	1700	1800
Height	mm	2150	2350	2480

Items	unit	QC11Y-12x2500	QC11Y-12x3200	QC11Y-12x4000
Max. cutting thickness	mm	12	12	12
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-2	0.5-2	0.5-2
Travel distance of back gauge	mm	20-800	20-800	20-800
Throat depth	mm	150	150	150
Stroke speeds	spm	12-16	10-16	10-15
Main motor	kW	15	15	18.5
Length	mm	3140	4000	4800
Width	mm	1800	1800	2000
Height	mm	2250	2550	2650

Items	unit	QC11Y-16x2500	QC11Y-16x3200	QC11Y-16x4000
Max. cutting thickness	mm	16	16	16
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-2.5	0.5-2.5	0.5-2.5
Travel distance of back gauge	mm	20-800	20-800	20-800
Throat depth	mm	150	150	150
Stroke speeds	spm	10-16	10-16	10-15
Main motor	kW	22	30	30
Length	mm	3140	3880	4800
Width	mm	2000	2150	2150
Height	mm	2520	2650	2650

Items	unit	QC11Y-20x2500	QC11Y-20x3200	QC11Y-20x4000
Max. cutting thickness	mm	20	20	20
Max. cutting width	mm	2500	3200	4000
Tensile strength of plate to be cut	N/mm2	450	450	450
Cutting angle	deg	0.5-2.5	0.5-2.5	0.5-2.5
Travel distance of back gauge	mm	20-800	20-800	20-800
Throat depth	mm	150	150	150
Stroke speeds	spm	10-15	10-15	8-12
Main motor	kW	30	30	30
Length	mm	3140	3880	4800
Width	mm	2250	2250	2250
Height	mm	2520	2700	2880

Shanghai Yingxin World Machinery Co., Ltd
Add: 12F, 432 Huaihai Road West, Shanghai, China
Tel: 0086-21-62828320 62828873 Fax: 0086-21-62829970
Http:// www.worldpowerpress.com E-mail: info@worldpowerpress.com